

Product Information Packet

February 5, 2024

Data shown is for the current revision model #. Ensure your nameplate model # matches.

Model Number:	WPN-DA182TSH-6C
Catalog Number:	BA6N1.5V4JM
Connection Diagram:	See Page 4
Outline Drawing:	See Page 3

Table of Contents

Specification	01
Performance Characteristics	02
Outline Drawing	03
Connection Drawing(s)	04

Marks:

MODEL NUMBER:	BA6N1.5V4JM	Estimated Weight:	100 Lbs
Outline Drawing:	See Page 3	Time Rating:	S1
Connection Diagram:	See Page 4	Enclosure:	TEFC
Design Code:	B	Encl Construction:	GP
Type:	KS	Ambient Max(°C):	40
Frame:	182JM	Alt Ambient Max(°C):	40
Phases:	3	Insulation Class:	F
Poles:	6	NEMA Design:	B
Output Power:	1.5HP	Nominal Efficiency:	87.5 %
RPM:	1170	Guaranteed Efficiency:	85.5 %
Voltage:	208-230/460	3/4 Load Efficiency:	87.4 %
Hertz:	60	KVA Code:	H
Amps - FL:	4.44/2.22	Max KVAR:	7.1
Service Factor:	1.25@60Hz	Power Factor:	71%
Alt Service Factor:	1.15	Bearing - DE:	6206-ZZC3
		Bearing - ODE:	6205-ZZC3

Enclosure is Totally Enclosed Fan-Cooled

Stamped Nameplate Notes:

12-60HZ CONSTANT TORQUE, 6-60Hz VARIABLE TORQUE

50HZ DATA:
190-200/400V
5.52/2.76AMPS
RPM 975
SF 1.0

CSA APPROVED FOR CLASS I;DIVISION 2; GROUPS A, B, C & D,ZONE 2; GROUPS IIA & IIB T3 WITH VFD

Additional Information:

F1/F2/F3/ROUND BODY MOUNTING USING REMOVABLE/REPOSITIONABLE FEET
INVERTER DUTY: CT5:1(12Hz~60Hz)@100%TN, CT15:1(4Hz~60Hz)@66.7%TN, VT20:1

Performance Characteristics


Marks:

LOAD %	150.0	125.0	100.0	75.0	50.0	25.0
% EFF	85.7	86.9	87.5	87.4	85.8	79.2
% PF	77.7	75.4	71.0	67.0	50.6	30.4
AMPS(460V)	3.1	2.6	2.2	1.8	1.6	1.4

TORQUE(FL) LB-FT 6.6 TORQUE(LR)%FL 175 TORQUE(BD)%FL 290
 AMPS(LR 460V) 13.13 PF AT START 27

Other Useful Information for Application:

Rotor Inertia: Lb-Ft ² (Kg-m ²):	0.369(0.015)
Max load inertia: Lb-Ft ² (Kg-m ²):	
Load Type:	Square Torque/Speed Characteristic
Voltage:	100%
Number of starts per hour:	2 Cold or 1 Hot
Acceleration Time with maximum inertia (sec):	6.1
Safe stall time (sec): Cold/Hot	74/30



Marks:

Connection Diagram

