



Product Information Packet

April 1, 2024

Data shown is for the current revision model #. Ensure your nameplate model # matches.

Model Number:	WPN-DF444TSD-2
Catalog Number:	BC2N125V9
Connection Diagram:	See Page 4
Outline Drawing:	See Page 3

Table of Contents	
Specification	01
Performance Characteristics	02
Outline Drawing	03
Connection Drawing(s)	04

Marks:

MODEL NUMBER:	BC2N125V9	Estimated Weight:	1512Lbs
Outline Drawing:	See Page 3	Time Rating:	S1
Connection Diagram:	See Page 4	Enclosure:	TEFC
Design Code:	B	Encl Construction:	GP
Type:	KS	Ambient Max(°C):	40
Frame:	444TS	Alt Ambient Max(°C):	40
Phases:	3	Insulation Class:	F
Poles:	2	NEMA Design:	B
Output Power:	125HP	Nominal Efficiency:	95.0%
RPM:	3575	Guaranteed Efficiency:	94.1%
Voltage:	460	3/4 Load Efficiency:	95.0%
Hertz:	60	KVA Code:	G
Amps - FL:	264/132	Max KVAR:	6.3
Service Factor:	1.25@60Hz	Power Factor:	90%
Alt Service Factor:	1.15	Bearing - DE:	6316-C3
		Bearing - ODE:	6316-C3

Enclosure is Totally Enclosed Fan-Cooled

Stamped Nameplate Notes:

12-60HZ CONSTANT TORQUE, 6-60Hz VARIABLE TORQUE

50HZ DATA:
 400V
 152AMPS
 RPM 2975
 SF 1.0

CSA APPROVED FOR CLASS I;DIVISION 2; GROUPS A, B, C & D,ZONE 2; GROUPS IIA & IIB T3 WITH VFD

Additional Information:

F1/F2/F3/ROUND BODY MOUNTING USING REMOVABLE/REPOSITIONABLE FEET
 INVERTER DUTY: CT5:1(12Hz~60Hz)@100%TN, CT15:1(4Hz~60Hz)@66.7%TN, VT20:1

Performance Characteristics


Marks:


LOAD %	150.0	125.0	100.0	75.0	50.0	25.0
% EFF	94.3	94.7	95.0	95.2	95.0	93.4
% PF	89.3	90.1	90.4	89.6	86.5	73.4
AMPS(460V)	201	165	132	99.3	68.7	41.2

TORQUE(FL) LB-FT 240 TORQUE(LR)%FL 150 TORQUE(BD)%FL 287
 AMPS(LR 460V) 792 PF AT START 43

Other Useful Information for Application:


Rotor Inertia: Lb-Ft ² (Kg-m ²):	20.6(0.866)
Max load inertia: Lb-Ft ² (Kg-m ²):	
Load Type:	Square Torque/Speed Characteristic
Voltage:	100%
Number of starts per hour:	2 Cold or 1 Hot
Acceleration Time with maximum inertia (sec):	23
Safe stall time (sec): Cold/Hot	43/25






Marks:

Thermistor Connection



6 LEAD CONNECTION - NEMA

**FOR WYE DELTA STARTER CONNECT
STAR START - DELTA RUN**



DIRECT ON LINE

