

Product Information Packet

April 9, 2025

Data shown is for the current revision model #. Ensure your nameplate model # matches.

Model Number:	WPN-DF447TSW-4
Catalog Number:	BC4N200V9C
Connection Diagram:	See Page 4
Outline Drawing:	See Page 3

Table of Contents

Specification	01
Performance Characteristics	02
Outline Drawing	03
Connection Drawing(s)	04

Marks:

MODEL NUMBER:	BC4N200V9C	Estimated Weight:	2300Lbs
Outline Drawing:	See Page 3	Time Rating:	S1
Connection Diagram:	See Page 4	Enclosure:	TEFC
Design Code:	B	Encl Construction:	GP
Type:	KS	Ambient Max(°C):	40
Frame:	447TS	Alt Ambient Max(°C):	40
Phases:	3	Insulation Class:	F
Poles:	4	NEMA Design:	B
Output Power:	200HP	Nominal Efficiency:	96.2%
RPM:	1785	Guaranteed Efficiency:	95.4%
Voltage:	460	3/4 Load Efficiency:	96.2%
Hertz:	60	KVA Code:	G
Amps - FL:	228	Max KVAR:	6.3
Service Factor:	1.25@60Hz	Power Factor:	86%
Alt Service Factor:	1.15	Bearing - DE:	6319-C3
		Bearing - ODE:	6319-C3

Enclosure is Totally Enclosed Fan-Cooled

Stamped Nameplate Notes:

12-60HZ CONSTANT TORQUE, 6-60Hz VARIABLE TORQUE

50HZ DATA:
400V
264AMPS
RPM 1485
SF 1.0

CSA APPROVED FOR CLASS I;DIVISION 2; GROUPS A, B, C & D,ZONE 2; GROUPS IIA & IIB T3 WITH VFD

Additional Information:

F1/F2/F3/ROUND BODY MOUNTING USING REMOVABLE/REPOSITIONABLE FEET
INVERTER DUTY: CT5:1(12Hz~60Hz)@100%TN, CT15:1(4Hz~60Hz)@66.7%TN, VT20:1

Performance Characteristics


Marks:

LOAD %	150.0	125.0	100.0	75.0	50.0	25.0
% EFF	95.4	95.9	96.2	96.3	96.2	94.9
% PF	84.8	85.8	86.0	84.4	79.2	60.7
AMPS(460V)	349	286	228	174	124	81.7

TORQUE(FL) LB-FT 803 TORQUE(LR)%FL 149 TORQUE(BD)%FL 237
 AMPS(LR 460V) 1249 PF AT START 31


Other Useful Information for Application:

Rotor Inertia: Lb-Ft ² (Kg-m ²):	60.7(2.55)
Max load inertia: Lb-Ft ² (Kg-m ²):	
Load Type:	Square Torque/Speed Characteristic
Voltage:	100%
Number of starts per hour:	2 Cold or 1 Hot
Acceleration Time with maximum inertia (sec):	28.5
Safe stall time (sec): Cold/Hot	42/25




Marks:

Thermistor Connection



6 LEAD CONNECTION - NEMA

**FOR WYE DELTA STARTER CONNECT
STAR START - DELTA RUN**



DIRECT ON LINE

