



## 60HZ TECHNICAL DATA SHEET

CATALOG No: **HO4N005-4C**

ISSUED: 20-Mar-24

**GENERAL INFORMATION**

HP	KW	Pole	RPM	Frame	Voltage	Hz	Phase	IP Rating
5	-	4	1800	184TC	230/460 V	60	3	IP23

Enclosure	Ins. Class	Service Factor	Time Rating	NEMA Design	Rated Amb.	Rated Altitude
ODP	F	1.15	Continuous	B	-15 to 40 C*	<3300 ft

**TYPICAL PERFORMANCE**

Efficiency (%)			Power Factor (%)	
Full Load	3/4 Load	1/2 Load	Full Load	
90.2	91.0	91.0	82.00	

Full Load Amps 460 V	Full Load RPM
6.3	1750


NEMA KVA Code	Bearing Size	
	Drive End	Non-Drive End
H	6306.00	6205.00

\*Weights shown are estimated and based on standard foot mounted motor designs


**VFD DUTY INFORMATION**

Variable Torque	Rating
6 - 60 Hz	Open Drip Proof
-	

Notes:



						<p><b>BROOK CROMPTON</b> Keeping Industry Turning</p>				
MARK	NUMBER	DOCUMENTARY NUMBER	SIGN	DATE			DRAWING MARK	NUMBER	WEIGHT	PROPORTION
DESIGN			TECHNICS							1:3
DRAWN			STANDARD-IZATION							
COLLATE			APPROVE				TOTAL PAGE	NO.		
AUDITING			DATE			N180TC;ODP				



VOLTAGE	L1	L2	L3	JOIN
LOW	T1,T7	T2,T8	T3,T9	T4&T5&T6
HIGH	T1	T2	T3	T4&T7; T5&T8; T6&T9

Description  
 CONNECTION DIAGRAM, NEMA MARKINGS  
 DUAL VOLTAGE, SERIES-PARALLEL STAR

Drawing No.  
 9L-07827-N

