

60HZ TECHNICAL DATA SHEET

CATALOG No: **HO6N075-4C**

ISSUED: 20-Mar-24

GENERAL INFORMATION

HP	KW	Pole	RPM	Frame	Voltage	Hz	Phase	IP Rating
75	-	6	1200	405TC	230/460 V	60	3	IP23

Enclosure	Ins. Class	Service Factor	Time Rating	NEMA Design	Rated Amb.	Rated Altitude
ODP	F	1.15	Continuous	B	-15 to 40 C*	<3300 ft

TYPICAL PERFORMANCE

Efficiency (%)			Power Factor (%)	
Full Load	3/4 Load	1/2 Load	Full Load	
94.5	94.1	93.0	75.00	

Full Load Amps 460 V	Full Load RPM
99.5	1190


NEMA KVA Code	Bearing Size	
	Drive End	Non-Drive End
F	6316.00	6314.00

*Weights shown are estimated and based on standard foot mounted motor designs

VFD DUTY INFORMATION


	Variable Torque	Rating
-	6 - 60 Hz	Open Drip Proof
-	-	

Notes:



STAR/WYE START — DELTA RUN

VOLTAGE		L1	L2	L3	JOIN
LOW	START	T1,T7	T2,T8	T3,T9	T4&T5&T6 T10&T11&T12
	RUN	T1,T6, T7,T12	T2,T4, T8,T10	T3,T5, T9,T11	
HIGH	START	T1	T2	T3	T4&T7; T5&T8; T6&T9; T10&T11&T12
	RUN	T1,T12	T2,T10	T3,T11	T4&T7; T5&T8; T6&T9



DIRECT ON LINE

VOLTAGE	L1	L2	L3	JOIN
LOW	T1,T6, T7,T12	T2,T4, T8,T10	T3,T5, T9,T11	
HIGH	T1,T12	T2,T10	T3,T11	T4&T7; T5&T8; T6&T9

Description
CONNECTION DIAGRAM, NEMA MARKINGS
DUAL VOLTAGE, SERIES—PARALLEL DELTA

Drawing No.
12L—33582—N